# **Product information**

# Pro-Line Electronic Spray

# PI 32/10/30/2023

# **Description**

Fully synthetic Electronic Spray that is compatible with plastics for the cleaning and care of contaminated electrical parts. Protects the electronic parts against corrosion by driving out moisture and water. Infiltrates the oxide and sulfide layers, thereby reducing contact resistance, protecting the electronic parts and ensuring operational reliability. No adverse effects on plastic and rubber components. The quickdrying formula does not leave residues and is siliconefree.



- reduces contact resistance
- leaves no residues
- neutral behavior on rubber and plastics
- silicone-free
- also suitable for overhead work
- good corrosion protection
- penetrates and drives out moisture
- cleans contaminated contacts

#### Technical data

Color / appearance blue synthetic oil Base Viscosity at 40 °C 49,5 mm<sup>2</sup>/s Viscosity at 100 °C  $7 \text{ mm}^2/\text{s}$ Viscosity index 145 -53 °C Pour point DIN ISO 3016 2.1 Gew.-% Evaporation loss (Noack)

**DIN ISO 2909** Water content 40 ppm  $\Omega \cdot cm$ 

DIN 51 581

Neutralization number 0,03 mg KOH/g DIN 51 777 T 1

0-1 Copper corrosion

DIN 51 809

 $1.6 \cdot 10^9 \,\Omega \cdot cm$ 

Specific electrical volume

resistance at 20 °C

Odor characteristic

Form liquid

## Areas of application

Used for the maintenance, care, cleaning and protection of all electrical components on the vehicle such as plug and terminal connections, lamp sockets, cable distribution boxes, switch elements, relays, ignition distributors, contact breakers, starters, alternators, fuses, battery terminals and antennae and



for the lubrication of fine mechanical parts.

## **Application**

Spray electric components before assembly, then assemble. With severely corroded contacts, allow to act for longer. Rub off loosened corrosion residues with a cloth or brush. The fold-out capillary tube ensures precision spraying. With the capillary tube folded in, large areas are sprayed. Also sprays when inverted. Note: After spraying on, allow a flash-off period of 10 min. before connecting the component to a power supply.

### Available pack sizes

400 ml Can aerosol

D-GB-I-E-P

400 ml Can aerosol 9913

GB-DK-FIN-N-S

400 ml Can aerosol 20674

D-NL-F-GR-RUS

Our information is based on thorough research and may be considered reliable, although not legally binding.